

FIG.1




FIG.2




FIG.3

DESTINATION	PROCESSED
RECEPTION DESK	×
EMBARKATION CHECK DESK	
BOARDING GATE	
...	

FIG.4

221

DEVICE ID	DEVICE TYPE	INSTALLATION STATE			USE STATE	SELECTED COLOR	IP ADDRESS
		X	Y	DIRECTION θ			
1	DISPLAY	2000	2000	(0,1,0)	VACANT	—	201.152.13.1
2	PROJECTOR	3000	2000	(0,0,1)	VACANT	—	201.152.13.2
3	PROJECTOR	2000	3000	(1,0,0)	IN USE	YELLOW	201.152.13.3
...							

FIG. 5




FIG.6

6/15




FIG.7

7/15

<u>231</u>						
SERIAL NUMBER	OSCILLATOR ID	RECEIVER ID-A	MEASURED VALUE A	RECEIVER ID-B	MEASURED VALUE B	RECEIVER ID-C
1	12345	23	6430	34	7100	24
2	2468	17	5500	18	6450	35
3	13579	18	4680	19	5890	42
...

FIG.8

232

RECEIVER ID	POSITION		
	X	Y	Z
1	2000	2000	5000
2	3000	2000	5000
3	2000	3000	5000
...

FIG.9




FIG.10




FIG.11




FIG.12




FIG.13




FIG. 14




FIG. 15

15/15

